

The biggest internal space in its class

UDHOME2 floor socket

- Support with a 54° slope in the interior
- Increased installation space
- Even large connectors disappear under the closed cover



With **UDHOME2**, OBO Bettermann has launched a more advanced version of a bestseller onto the market. The smallest floor socket has been optimised in terms of space, with virtually the same external dimensions.

www.obo-bettermann.com

Building Connections

OBO
BETTERMANN

Comparison of the UDHOME2 versions



	UDHOME2	UDHOME2 2020	
General data	Dimensions of floor sockets	125 x 125 mm	140 x 140 mm
	Height-adjustment range	95–115 mm 110–130 mm	100–135 mm 110–135 mm
	Empty pipe entries	4 for each installation area (heavy current / data technology)	4 for each installation area (heavy current / data technology), additional entries in the base of the UDHOME2
	Material (cover/frame)	Stainless steel	Stainless steel
		-	Brass
	Load capacity according to EN50085-2-2	3,000 N – according to resistance to vertical loads affecting a small surface area	3,000 N – according to resistance to vertical loads affecting a small surface area
Cover	Version	Decorative cover	Decorative cover
		Floor covering recess, 15 mm	Floor covering recess, 15 mm
	Opening mechanism	Fixed hinge	Flexible cover insert, can be used in all directions
	Locking mechanism	No	Ball snapper for soft cover closing
	Cord outlet	With opening contour	With handle clamp
	Cord outlet cross-section	-	Increased by 20% for optimised cable outlet
	Exchangeable cord outlet	No	Yes (version available with opening contour and handle clamp as an accessory)
	Exchangeable cover	No	Yes, the cover can be replaced on account of the identical construction
	Mounting protection cover	Yes	Yes, with OBO logo and mounting instructions
	IP class according to EN50085-2-2	IP20 when used IP40 when not used	IP20 when used IP40 when not used
Installation space	Number of sockets	Double M45 VDE/NF	Double M45 VDE/NF
		Empty	Empty
	Amount of data technology	2 with optional support	2 with optional support
	Straight connectors	No	Yes
	Angular connectors	Yes	Yes
	Suitable for most mobile phone chargers	No	Yes
	Cover can be closed with all connector types	No	Yes, thanks to the support sloping at 54° in the interior
	Height of installation space	Solid	Increases for greater height adjustments
	Mounting support material	Galvanised sheet steel	Stainless steel
	Edge processing	No	Yes (soft edges)
CE conformity	Yes	Yes	
VDE-certified	No	Yes	